



The Right Connection®

5206A API Adaptor

Application

- API Adaptors are used for bottom loading and unloading of petroleum tankers
- Permits the load at terminals and unload at the retail outlets for fuel unloading

Features

- Ergonomically designed straight handle with finger grips for enhanced control and comfort
- Maintenance is simplified, Dixon API Adaptors nose cone and poppet can be serviced without the need to remove the adaptor from the tanker
- Nose ring is anodized hard coat aluminium, providing years of trouble-free service.
- 1/2" FBSP sample port, drilled, tapped and plugged.
- Nose ring can be rotated to provide a fresh connection service.
- Removable handle

Material and Construction

- Aluminium body with anodized hard coat aluminium nose ring and stainless steel hardware
- Removable aluminium handle
- Baylast™ seals
- Nylon sight glass

Specifications

- Manufactured to American Petroleum Institute standard API RP-1004
- Length (poppet face to TTMA flange face) - 171mm
- Weight - 4.76kg



| Description | Part # |
|--|-----------|
| 4" API Adaptor c/w sight glass pull up to operate the handle | 5206A |
| 4" API Adaptor no sight glass pull up to operate the handle | 5206NGA |
| 4" API Adaptor c/w sight glass pull down to operate the handle | 5204NG |
| Replacement sight glass kit | 5204K8 |
| Sight glass blanking plate kit | 5204K9 |
| Anodised nose ring replacement | 5204K3 |
| 4" TTMA Baylast™ gasket seal | 400GTTFBL |
| 4" TTMA sight glass 25mm thick | DBSGF4-25 |

Dixon

1300 134 651
customerservice@dixonvalve.com.au
dixonvalve.com.au