# DATA SHEET

# A170 Heavy Duty Steel Air Delivery Hose

The Right Connection®

An exceptionally durable steel cord delivery hose engineered to convey high-pressure compressed air. Built to withstand extreme conditions and designed with high safety margins to ensure prolonged, dependable performance even in the most challenging work environments encountered in mines, quarries, construction, and industrial sites.



## **Hose Construction**

Tube:	
Cover:	
Reinforcing <sup>.</sup>	

NBR blend - black EPDM blend, smooth - yellow cing: High tensile steel wire cords

### Features

- Abrasion resistant
- Ozone resistant
- Weather resistant
- Oil mist resistant
- Mylar layline & embossed tape line
- Pin pricked cover
- Mandrel built

#### Temperature

-40°C to 70°C

# Standards

• Nil

#### Part Number

• To view available part number options please click here

Coil Lengths (mtr)	Weight (kg/mtr)	Bend Radius (mm)	Vacuum (bar)	Positive Working Pressure PSI / Bar				Dimensions	
				Burst		Working		(mm)	
				Bar	PSI	Bar	PSI	OD	ID
	<b>M</b>			×.		$\bigcirc$			IO
20	0.88	125	n/a	160	2320	40	580	36.0	25.4
20	1.54	190	n/a	160	2320	40	580	50.0	38.1
20	2.52	225	n/a	160	2320	40	580	66.0	50.8
20	3.36	315	n/a	160	2320	40	580	80.0	63.5
20	4.50	380	n/a	160	2320	40	580	94.0	76.2
20	6.77	510	n/a	160	2320	40	580	122.0	101.6

Product Code: DB04