

## Automatic Shut-Off Nozzles



114D

<b>Application:</b>	For card lock and truck refuelling stations
<b>Design:</b>	Venturi type auto shut-off. Detachable trigger ratchet
<b>Material:</b>	Aluminium construction with bronze trigger
<b>Flow Rate:</b>	80 gpm flow (requires min 7.5 gpm for auto shut-off)

Female Inlet Size (inch)	Spout Outlet Size (inch)	Part No.	Price \$
Pressure Nozzle With Spout			
1½ NPT	1¾	1124D	1296.77
1½ BSPT	1½	1124DBSPT	1296.77

**Price Group: BY**  
AS02

## Standard Utility Nozzles



900S

<b>Application:</b>	For use with 12 volt pumps & gravity flow fittings. For economy fuel dispensing, including construction, farm & small truck utility tanks.
<b>Design:</b>	Choice of spouts.
<b>Material:</b>	Diecast metal body
<b>Working Pressure:</b>	25 PSI
<b>Approvals:</b>	UL

Female Inlet Size (inch)	Spout Outlet Size (inch)	Part No.	Price \$
Aluminium			
1 NPT	1 outlet	900*	184.95
1 NPT	1 straight	900S	189.04
1 NPT	1 bent	900B	191.38
1 NPT	¾ straight	900W34S	189.76
1 NPT	¾ bent	900W34B	189.23
¾ NPT	¾ straight	900S34	213.41
¾ NPT	¾ bent	900B34	212.89

**Price Group: SD**  
AS02



900B

Description	Part No.	Price \$
Replacement Parts		
¾" replacement straight spout	234-80-4	19.10
¾" replacement bent spout	234-80-5	17.20
1" replacement straight spout	5875-4	POR
1" replacement bent spout	875-5	14.09
trigger	900TK	8.60
plunger and valve assemblies, cap, O-ring	900SK	25.60

\* Nozzle body only (without spout)  
Note: ¾" nozzle inlet uses 1" x ¾" reducer bushing, supplied.

**Price Group: SD**  
AS02



875-5



**NOTE:** Some fuel additives are not compatible with certain materials.  
Please contact Dixon™ for fuel compatibilities.