

## PVC All Rounder (Chemical, Air & Water)

<b>Application:</b>	Multi purpose UV stabilised hose for agricultural spraying and general purpose air and water
<b>Tube:</b>	Yellow PVC
<b>Reinforcing:</b>	Polyester
<b>Cover:</b>	Blue smooth PVC with yellow stripe
<b>Temperature Range:</b>	-10°C to 60°C
<b>Special Feature:</b>	UV stabilised



Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Length mtr	Price \$ per mtr / coil
	ID	OD	PSI	MPa					
H1400620	6	11.6	450	3.1	1350	72 <sup>1</sup>	0.13	20	48.66
H14006100	6	11.6	450	3.1	1350	72 <sup>1</sup>	0.13	100	243.31
H1400820	8	14.3	450	3.1	1350	96 <sup>1</sup>	0.15	20	66.07
H14008100	8	14.3	450	3.1	1350	96 <sup>1</sup>	0.15	100	330.35
H1401020	10	16.9	450	3.1	1350	120 <sup>1</sup>	0.17	20	71.77
H14010100	10	16.9	450	3.1	1350	120 <sup>1</sup>	0.17	100	358.83
H1401220	12	19.5	450	3.1	1350	144 <sup>1</sup>	0.20	20	91.14
H14012100	12	19.5	450	3.1	1350	144 <sup>1</sup>	0.20	100	455.66
H1402020	20	29	450	3.1	1350	240 <sup>1</sup>	0.43	20	170.87
H14020100	20	29	450	3.1	1350	240 <sup>1</sup>	0.43	100	854.35
H1402520	25	34	450	3.1	1350	300 <sup>1</sup>	0.56	20	252.89

Price Group: HP  
DA27

## PVC Divers / Air Breathers

<b>Application:</b>	Approved divers air breathing hose for professional and sports diving breathing apparatus eg breathing masks, aquaculture.
<b>Tube:</b>	White PVC
<b>Reinforcing:</b>	Polyester
<b>Cover:</b>	Yellow tint, clear smooth PVC
<b>Temperature Range:</b>	0°C to 60°C
<b>Special Feature:</b>	UV stabilised
<b>Standards:</b>	Conforms to AS/NZS 2299.1:1999 and AS/NZ1716 and applicable FDA standards



Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Length (mtr)	Price \$ per coil
	ID	OD	PSI	MPa					
H1000820	8	15	350	2.4	1400	96 <sup>1</sup>	0.15	20	118.91
H10008100	8	15	350	2.4	1400	96 <sup>1</sup>	0.15	100	594.56
H1001020	10	17.5	350	2.4	1400	120 <sup>1</sup>	0.18	20	146.78
H10010100	10	17.5	350	2.4	1400	120 <sup>1</sup>	0.18	100	733.91

Price Group: HP  
DA08

<sup>1</sup> Denotes figure is calculated as theoretical.

Complete hose data specification sheets are available upon request.

