

## Potter Pressure



WFSR-F



<b>End Connection:</b>	NPT Male
<b>Body Materials:</b>	Cover - die cast with red powder coat. Base - plated steel.
<b>Pressure:</b>	Refer to table below
<b>Approvals:</b>	UL, CSFM, FM, LPC Approved, CE marked
<b>Application:</b>	For monitoring high and/or low pressure variations.

Part No.	Type	Description	Price \$	
FFS-PS10-1A	i	PS10-1A	28-140 kPa - 1 Set of Contacts	POR
FFS-PS10-2A	i	PS10-2A	28-140 kPa - 2 Set of Contacts	688.22
FFS-PS40-1		PS40-1A	70-1225 kPa - 1 Set of Contacts	386.52
FFS-PS40-2A	i	PS40-2A	70-1225 kPa - 2 Set of Contacts	513.36
FFS-PS120-1A	i	PA120-1A	70-1225 kPa - 1 Set of Contacts Field Adjustable. Pressure drop model of 770kPa	942.01
FFS-PS120-2A	i	PS120-2A	70-1225 kPa 2 Set of Contacts Pressure Drop / Pressure Rise Mode Field Adjustable	657.79
FFS-WFSR-F	i	WFSR-F	Pressure Activated (water flow with retard)	2372.63
FFS-ADPS-LP	i	ADPS-LP	Adjustable dead band switch	POR
FFS-ADPS-HP		ADPS-HP	Range 70-2100kPa, 175-4200 kPa.	887.20

Price Group: SD

## Potter Anti-Tamper



OSYSU



PTS-C



Part No.	Type	Description	Price \$	
FFS-OSYSU-A1		OSYSU-1	To suit Gate Valves OS&Y DN50 - DN300, 1 Set Of Contacts	615.10
FFS-OSYSU-2	i	OSYSU-2	To suit Gate Valves OS & Y DN50 - DN300, 2 Set Of Contacts	POR
FFS-PTS-C	i	PTS - C	Pull out plug style suitable for any type of hand wheel operated valve	912.66

Price Group: SD

## Vane Type Waterflow Alarm Switch for Small Pipe (DN25-50)



VSR-SF



Part No.	Type	Price \$
FFS-VSR-FS-25	VSR-SFDN25 to DN50	726.26

Price Group: SD

## Vane Type Waterflow Alarm Switch



VSR-F



Size (to suit pipe NB)	Part No.	Price \$
50	FFS-WFI50	675.29
65	FFS-WFI65	726.26
80	FFS-WFI80	619.71
100	FFS-WFI100	i 495.97
150	FFS-WFI150	i 726.26
200	FFS-WFI200	i 1125.56
250	FFS-WFI250	i POR

Price Group: SD

VB07