

Potter Pressure



WFSR-F



End Connection:	NPT Male
Body Materials:	Cover - die cast with red powder coat. Base - plated steel.
Pressure:	Refer to table below
Approvals:	UL, CSFM, FM, LPC Approved, CE marked
Application:	For monitoring high and/or low pressure variations.

Part No.	Type	Description	Price \$
FFS-PS120-1A	i PA120-1A	70-1225 kPa - 1 Set of Contacts Field Adjustable. Pressure drop model of 770kPa	470.40
FFS-ADPS-HP	ADPS-HP	Range 70-2100kPa, 175-4200 kPa.	POR

Price Group: SD

Potter Anti-Tamper



OSYSU



PTS-C



Part No.	Type	Description	Price \$
FFS-OSYSU-A1	OSYSU-1	To suit Gate Valves OS&Y DN50 - DN300, 1 set of contacts	528.00
FFS-PTS-C	i PTS - C	Pull out plug style suitable for any type of hand wheel operated valve	864.00

Price Group: SD

Vane Type Waterflow Alarm Switch for Small Pipe (DN25-50)



VSR-SF



Part No.	Type	Price \$
FFS-VSR-FS-25	VSR-SFDN25 to DN50	720.00

Price Group: SD

Vane Type Waterflow Alarm Switch



VSR-F



Size (to suit pipe NB)	Part No.	Price \$
50	FFS-WFI50	624.00
65	FFS-WFI65	624.00
80	FFS-WFI80	i 624.00
100	FFS-WFI100	i 624.00
150	FFS-WFI150	i 720.00
200	FFS-WFI200	i 888.00

Price Group: SD

VB07

S
453 - 499