

PVC Safety Yellow

Application:	General purpose air and water supply with excellent flexibility and toughness. Resistant to oils
Temperature Range:	0°C to 60°C
Tube:	Black PVC
Reinforcing:	Polyester
Cover:	Yellow ribbed PVC
Special Features:	UV Stabilised
Standards:	¼ to 1½" - Exceeds AS/NZS 2554:1998 Class B for burst pressure. 2" - Exceeds AS/NZS 2554:1998 Class C for burst pressure.

Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius	Weight kg/mtr	Length (mtr)	Price \$ per mtr / coil
	ID	OD	PSI	MPa					
H0100620	6	12.0	250	1.7	1000	65	0.11	20	41.82
H01006100	6	12.0	250	1.7	1000	65	0.11	100	209.00
H0100820	8	14.0	250	1.7	1000	75	0.13	20	49.03
H01008100	8	14.0	250	1.7	1000	75	0.13	100	245.00
H0101020	10	17.0	290	2.0	1160	85	0.19	20	53.97
H01010100	10	17.0	290	2.0	1160	85	0.19	100	269.00
H0101220	12.5	19.0	250	1.7	1000	100	0.21	20	64.89
H01012100	12.5	19.0	250	1.7	1000	100	0.21	100	324.45
H0102020	20	28.0	230	1.6	920	150	0.40	20	112.27
H0102520	25	33.0	230	1.6	920	180	0.51	20	183.34
H0103220	32	42.0	230	1.6	920	220	0.76	20	319.30
H0104020	40	50.0	230	1.6	920	250	1.06	20	428.48
H0105020	50	63.0	290	2.0	1160	320	1.51	20	700.40

Price Group: HP

DA28

Complete hose data specification sheets are available upon request.

Phone: 1300 134 651
dixonvalve.com

ADPL2015

Part numbers marked "i" are non stock.
Enquire for availability.
All prices exclude GST.