DATA SHEET

A102 Rubber Contractors Air Delivery Hose

The Right Connection®

Crafted with a smooth yellow non-marking cover to enhance visibility, this cost-effective pneumatic air and water hose is tailored for diverse applications in construction, industrial, and agricultural fields. It's particularly well-suited for heavy-duty air compressor usage, seamlessly supporting a wide range of pneumatic equipment such as portable compressors, jackhammers, breakers, and stampers.

Hose Construction

Tube: SBR blend - black
Cover: SBR blend, smooth - yellow
Reinforcing: Polyester yarn

Features

- Oil mist resistant
- Ozone resistant
- Weather resistant
- Abrasion resistant
- Extruded

Temperature

- -25°C to 75°C

Standards

- Nil

Part Number

- To view available part number options please click here

Dimensions (mm)		Pressures				Vacuum (bar)	Bend Radius (mm)	Weight (kg/mtr)	Coil Lengths (mtr)
		Working		Burst					
ID	OD	PSI	Bar	PSI	Bar				
6.4	13.0	200	14	696	48	n/a	50	0.18	20, 100
9.5	17.0	200	14	696	48	n/a	75	0.26	20, 100
12.7	21.0	200	14	696	48	n/a	100	0.39	20, 100
15.9	26.0	200	14	696	48	n/a	125	0.56	20, 100
19.1	31.0	200	14	696	48	n/a	155	0.83	20, 100
25.4	37.0	200	14	696	48	n/a	205	0.92	20, 100

Product Group: DB43