DATA SHEET

A108 Single Welding Line Delivery Hose



Designed to fulfill AS1335 specifications, guaranteeing the safe transfer of oxygen (blue) or acetylene (red) for welding, cutting and allied processes across diverse industrial sectors.





Hose Construction

Tube: SBR blend - black

Cover: SBR blend, smooth - blue or red

Reinforcing: Polyester yarn

Features

- Ozone resistant
- Weather resistant
- Oil mist resistant
- · Pin pricked cover
- Extruded

Temperature

• -20°C to 70°C

Standards

• AS1335:1995

Part Number

• To view available part number options please click here

| Dimensions (mm) | | Pressures | | | | | | Bend | |
|-----------------|------|-----------|-----|-------|-----|-----------------|-----------------|--------|---------|
| | | Working | | Burst | | Vacuum (bar) | Weight (kg/mtr) | Radius | Coil |
| ID | OD | PSI | Bar | PSI | Bar | (50.) | (9,) | (mm) | Lengths |
| IO | | | | *** | |)(| € | | (mtr) |
| 4.8 | 12.0 | 217 | 15 | 870 | 60 | n/a | 0.14 | 40 | 100 |
| 6.4 | 13.0 | 217 | 15 | 870 | 60 | n/a | 0.15 | 50 | 100 |
| 9.5 | 16.0 | 217 | 15 | 870 | 60 | n/a | 0.19 | 75 | 100 |

Product Code: DB21