DATA SHEET

A430 Petrol & Oil Suction & Delivery Hose

The Right Connection®

FUELBOSS

Specially designed for the transfer of petroleum/oil products with a maximum of 50% aromatic content for both suction and delivery, typically used on tank trucks and in general industrial applications. Also suitable for use as hydraulic oil return lines and for marine wet exhaust and bilge pump connections.

Hose Construction

Tube: NBR - black
Cover: SBR/EPDM blend, smooth - black
Reinforcing: High tensile synthetic textile cords with double wire helix and anti-static copper wire

Features

- Ozone resistant
- Weather resistant
- Abrasion resistant
- Oil resistant
- Mylar layline & embossed tape line
- Mandrel built

Temperature

- -35°C to 80°C

Standards

- Nil

Part Number

- To view available part number options please click here

Dimensions (mm)		Pressures				Vacuum (Bar)	Bend Radius (mm)	Weight (kg/mtr)	Coil Lengths (mtr)
		Working		Burst					
ID	OD	PSI	Bar	PSI	Bar				
19.1	30	150	10	450	30	0.9	80	0.68	20
22.0	32	150	10	450	30	0.9	90	0.70	20
25.4	35	150	10	450	30	0.9	105	0.75	20, 60
31.8	43	150	10	450	30	0.9	135	1.12	20, 60
35.0	47	150	10	450	30	0.9	150	1.26	20
38.1	49	150	10	450	30	0.9	165	1.32	20, 60
42.0	54	150	10	450	30	0.9	195	1.47	20
45.0	57	150	10	450	30	0.9	205	1.56	20
48.0	62	150	10	450	30	0.9	215	1.84	20
50.8	63	150	10	450	30	0.9	230	1.75	20, 60
55.0	68	150	10	450	30	0.9	250	2.02	20
60.0	73	150	10	450	30	0.9	275	2.19	20
63.5	76	150	10	450	30	0.9	290	2.42	20
70.0	83	150	10	450	30	0.9	330	2.71	20
76.2	89	150	10	450	30	0.9	360	2.92	20
90.0	105	150	10	450	30	0.9	440	3.68	20
102.0	118	150	10	450	30	0.9	510	4.90	20
127.0	145	150	10	450	30	0.9	650	6.73	20
152.4	172	150	10	450	30	0.9	790	8.87	20
203.0	224	150	10	450	30	0.9	1010	12.89	20

Product Code: DB15

customerservice@dixonvalve.com.au . 1300 134 651