DATA SHEET A452 Fuel Reeling Delivery Hose



Specially designed for the transfer of petroleum/oil products with a maximum of 50% aromatic content. Typically used on tank trucks and in reeling applications requiring compliance with EN1360 Type 1.



Hose Construction

Tube:NBR conductive - blackCover:CR conductive, smooth - blackReinforcing:High tensile synthetic textile cords

Features

- Ozone resistant
- Weather resistant
- Abrasion resistant
- Oil resistant
- Mylar layline & embossed tape line
- Conductive tube & cover
- Mandrel built

Temperature

• -30°C to 70°C

Standards

• EN 1360 - Type 1 - Ω Grade (conductive tube and cover)

Part Number

• To view available part number options please click here

Dimensions (mm)		Pressures					Bend		
		Working		Burst		Vacuum (bar)	Radius	Weight (kg/mtr)	Coil
ID	OD	PSI	Bar	PSI	Bar	()	(mm)	(Lengths
IO		\bigcirc		×)((mtr)
25.4	36.0	230	16	696	48	n/a	150	0.74	30, 60
31.8	44.0	230	16	696	48	n/a	175	1.10	30, 60
38.1	51.0	230	16	696	48	n/a	225	1.24	30, 60
50.8	67.0	230	16	696	48	n/a	350	1.64	30, 60
								Produ	ct Code: DB1