DATA SHEET **AUSBHD Petrol & Oil Suction & Delivery Hose**



Traditionally utilised for liquid waste transfer, as well as grease trap and septic tank cleaning, this hose is also highly effective as a standard water suction delivery hose. Its PVC/rubber alloy construction ensures excellent flexibility, even in cooler climates.



Hose Construction

Tube: PVC/NBR blend smooth - blue Cover: PVC/NBR blend smooth - blue Reinforcing: Rigid PVC embedded helix - White

Features

- UV stabilised
- Abrasion resistant
- Oil resistant
- High impact resistance
- Extruded

Temperature

• -40°C to 65°C

Standards

Nil

Part Number

• To view available part number options please click here

Dimensions (mm)		Pressures						Bend	
		Working		Burst		Vacuum (bar)	Weight (kg/mtr)	Radius	Coil
ID	OD	PSI	Bar	PSI	Bar	(201)	(9,)	(mm)	Lengths
IO)(€ W		(mtr)
25.4	31.5	90	6	260	18	1.0	0.39	75	20
31.8	39.1	80	5.5	240	16.5	1.0	0.51	105	20
38.1	46.2	75	5	220	15	1.0	0.65	155	20
50.8	60.7	75	5	220	15	1.0	1.10	205	20
63.5	74.4	75	5	220	15	1.0	1.50	255	20
76.2	87.1	60	4	180	12	1.0	1.80	305	20
101.6	115.1	50	3.5	150	10.5	1.0	3.00	380	20
152.4	169.4	30	2	90	6	1.0	5.51	635	20

Product Code: DA12