DATA SHEET

A210 Water Suction & Delivery Hose

The Right Connection®

AQUABOSS

Designed with a lightweight yet durable construction making it perfect for both suction and delivery of water and non-corrosive liquids in mining, construction, irrigation, and municipal applications. Also used for the transfer of compressed air.

Hose Construction

Tube: SBR - black
Cover: SBR/EPDM blend - black
Reinforcing: High tensile synthetic textile cords and steel wire helix

Features

- Ozone resistant
- Weather resistant
- Abrasion resistant\
- Mylar layline & embossed tape line
- Mandrel Built

Temperature

- -30°C to +80°C

Standards

- Nil

Part Number

- To view available part number options please click here

Dimensions (mm)		Positive Working Pressure PSI / Bar				Vacuum	Weight (kg/mtr)	Bend Radius (mm)	Coil Length (mtr)
		Working		Burst					
ID	OD	psi	bar	psi	bar	bar			
19.1	28	150	10	435	30	0.93	0.58	70	20
25.4	34	150	10	435	30	0.93	0.70	95	20
31.8	42	150	10	435	30	0.93	1.00	125	20
38.1	48	150	10	435	30	0.93	1.23	150	20
50.8	62	150	10	435	30	0.93	1.70	215	20
63.5	75	150	10	435	30	0.93	2.17	280	20
76.2	89	150	10	435	30	0.93	3.01	350	20
90.0	105	150	10	435	30	0.93	4.00	440	20
101.6	115	150	10	435	30	0.93	4.27	490	20
127.0	142	150	10	435	30	0.93	5.87	650	20
152.4	168	150	10	435	30	0.93	7.68	760	20
203.2	222	150	10	435	30	0.93	12.33	1120	20
254.0	275	150	10	435	30	0.93	17.74	1525	20

Product Code: DB16