King Cable™ Safety Whipcheck



King Safety cables prevent hose whip in the event of the accidental separation of a coupling or clamp device. The steel cables span the hose fittings to provide standby safety for the hose. Spring-loaded loops in the cable ends are easily opened to passover the couplings and provide a firm grip on the hose.





Features

- King safety cable reaches across the hose fittings to provide safety for hose application
- Thoroughly tested with years of service. A positive safeguard for hose connections - helps you meet today's safety standards
- Highly resistant to rust and corrosion
- Minimises damage to equipment and injuries to operators in the event hose, couplings or clamps fail, or there is an accidental separation of the assembly
- · Hose-to-hose or hose-to-rigid outlet

Construction

- · Wire Rope Galvanised Carbon Steel
- · Ferrules Aluminium
- · Springs Galvanised Carbon Steel

Installation and Safety Notes

- Must be installed in the extended position (no slack)
- · No tools needed easy to install and remove

HOSE-TO-TOOL SERVICE

Part Number		Size			Maximum Working Pressure
Steel	Stainless Steel	Cable (mm)	Hose ID (mm)	Length (mm)	PSI
WSR1	WSR1SS	3	13 - 32	515	200
WSR3	-	5	13 - 50	712	200
WSR2	WSR2SS	6	38 - 75	956	200
WSR4	-	10	100	1118	200

HOSE-TO-HOSE SERVICE

Part Number		Size			Maximum Working Pressure
Steel	Stainless Steel	Cable (mm)	Hose ID (mm)	Length (mm)	PSI
WB1	WB1SS	3	13 - 32	515	200
<u>WB3</u>	-	5	13 - 50	712	200
WA2	WA2SS	6	38 - 75	956	200
WA4	-	10	100	1118	200

Product Group:AD03

© 2020 APAC • King Cable_November2021

Dixon

1300 134 651

customerservice@dixonvalve.com.au

dixonvalve.com.au