DATA SHEET FloMAX Flush Face **Connectors**



Features:

- New patented design uses an internally sealed ball lock mechanism to ensure a clean and trouble free performance
- All flush face connectors have the exact same outside dimensions and weight
- 12 colour choices and sizes are available along with a universal evacuation nozzle
- Can be connected without pulling on the nozzle pull
- Flush face nozzle and receiver available in JIC base configuration on request
- Can be connected or disconnected under pressure
- The high flow, patented non-interchangeable feature means each colour will only mate with its corresponding coloured receiver or nozzle
- 1500 PSI working pressure when coupled
- 50 GPM flow rate

Material:

Aircraft grade aluminium and hardened stainless steel

Size:

3/4" male NPT



Flush Face Nozzle



Flush Face Receiver





NOTE: All receivers supplied with cap and lanyard

Nozzle	Receiver	Colour
FLN-1	FLR-C-1	Red
FLN-2	FLR-C-2	Gold
FLN-3	FLR-C-3	Teal
FLN-4	FLR-C-4	Violet
FLN-5	FLR-C-5	Navy
FLN-6	FLR-C-6	Brown
FLN-7	FLR-C-7	Blue/Grey
FLN-8	FLR-C-8	Clear
FLN-9	FLR-C-9	Green
FLN-10	FLR-C-10	Grey
FLN-11	FLR-C-11	Bronze
FLN-12	FLR-C-12	Orange
FLN-16EVAC	-	Flush Face Evacuation Nozzle NPT
FLNJ-EVAC	-	Flush Face Evacuation Nozzle JIC

1300 134 651 | dixonvalve.com.au