DATA SHEET

Fire Hydrant Landing Valves

British Instantaneous (BI) - WA/NT

The Right Connection®

BI Roll Grooved/BSP Female

BI BSP Male

Features

- Outlet - DN65 BI (British Instantaneous) female
- Available inlet options - DN80 roll groove with internal DN65 BSP female thread
- DN65 BSP male thread
- Complete with plastic plug and chain

Specifications

- DN65 BI to BS336
- DN80 machined roll grooved to ANSI/AWWA C606
- DN65 BSP threads to ISO 7.1
- 1400kPa working pressure, 3200kPa test pressure
- Tested pressure loss AS2419.3 part 4.3.4 <25kPa @ 10L/S

Approvals

- Watermark certification
- Compliant with AS2419.2

Installation

- Suitable for both vertical and horizontal mounting to AS2419.1

Materials

- DR brass body in accordance with AS2345 and AS1565

BI Roll Grooved/BSP Female - Western Australia & Northern Territory

Part Number	Size (NB)		Material
	Outlet	Inlet	
FFS-LVBI-RG	DN65 BI female	DN80 roll grooved with internal DN65 BSP female thread	DR Brass

BI BSP Male - Western Australia & Northern Territory

Part Number	Size (NB)		Material
	Outlet	Inlet	
FFS-LVBI-BSP	DN65 BI female	DN65 BSP male	DR Brass

Dixon
1300 134 651
customerservice@dixonvalve.com.au
dixonvalve.com.au

November2025