DATA SHEET

Fire Hydrant Landing Valves

Queensland Round Thread (QRT) - QLD

The Right Connection®

QRT Roll Grooved/BSP Female

QRT BSP Male

Features

- Outlet - DN65 QRT (Queensland round thread) male
- Inlet options:
  - DN80 roll grooved with internal DN65 BSP female thread,
  - DN65 BSP male thread
- Complete with plastic cap and chain

Specifications

- QRT - 2TPI 12.7 pitch
- DN80 machined roll groove to ANSI/AWWA C606
- DN65 BSP threads to ISO 7.1
- 1400kPa working pressure, 3200kPa test pressure
- Tested pressure loss AS2419.3 part 4.3.4 <25kPa @ 10L/S

Approvals

- Watermark certification
- Compliant with AS2419.2

Installation

- Suitable for both vertical and horizontal mounting to AS2419.1

Materials

- DR brass body in accordance with AS2345 & AS1565

QRT Roll Grooved/BSP Female - Queensland

Part Number	Size (NB)		Material
	Outlet	Inlet	
FFS-LVQRT-RGB	DN65 QRT male	DN80 roll grooved with internal DN65 BSP female thread	DR Brass

QRT BSP Male - Queensland

Part Number	Size (NB)		Material
	Outlet	Inlet	
FFS-LVQRT-65B	DN65 QRT male	DN65 BSP male thread	DR Brass

Dixon
1300 134 651
customerservice@dixonvalve.com.au
dixonvalve.com.au

November2025