DATA SHEET

Fire Hydrant Landing Valves

Storz - NSW/SA/VIC/TAS

Storz 90°

Storz 135°

Features

- Outlet - DN65 Storz aluminium adaptor - forged NEN3374
- Inlet - DN80 roll groove with internal DN65 BSP female thread
- Complete with plastic cap and cable

Specifications

- DN65 Storz aluminium adaptor - forged NEN3374
- DN80 machined roll groove to ANSI/AWWA C606
- DN65 BSP female thread to ISO 7.1
- 1400kPa working pressure, 3200kPa test pressure
- Tested pressure loss AS2419.3 part 4.3.4 <25kPa @ 10L/S

Approvals

- Watermark certification
- Compliant with AS2419.2

Installation

- Suitable for both vertical and horizontal mounting to AS2419.1

Materials

- DR brass body in accordance with AS2345 and AS1565

Storz 90° - New South Wales & South Australia

Part Number	Size (NB)		Material
	Outlet	Inlet	
FFS-LV-STORZ90	DN65 Storz	DN80 roll grooved with internal DN65 BSP female thread	DR Brass

Storz 135° Oblique - Victoria & Tasmania

Part Number	Size (NB)		Material
	Outlet	Inlet	
FFS-LV-STORZ	DN65 Storz	DN80 roll grooved with internal DN65 BSP female thread	DR Brass

Dixon
1300 134 651
customerservice@dixonvalve.com.au
dixonvalve.com.au

November2025