



FloMAX Fuelling System Catalogue

Uncommon Excellence

FloMAX Fuelling System FloMAX Fuelling System 3

FloMAX Fuelling System - Diesel Fuel Nozzle	3
FloMAX Fuelling System - Diesel Fuel Receivers.....	3
Non-Interchange Diesel Fuel Nozzle and Receiver.....	4
FloMAX Fuelling System - Diesel High-Flow Fuel Nozzle.....	4
FloMAX Fuelling System - Diesel High-Flow Fuel Receiver	4
FloMAX Fuelling System - Diesel Fuel Swivels.....	5
FloMAX Fuelling System - Gravity Fill Receivers.....	5
FloMAX Fuel Vent System.....	5
FloMAX Standard Series Connectors - Engine Oil (Red)	6
FloMAX Standard Series Connectors - Coolant Fluid (Teal).....	6
FloMAX Standard Series Connectors - Hydraulic Oil (Gold)	7
FloMAX Standard Series Connectors - Transmission Fluid (Violet)....	7
FloMAX R-Series Connectors - Engine Oil (Red)	8
FloMAX R-Series Connectors - Coolant Fluid (Teal).....	8
FloMAX R-Series Connectors - Hydraulic Oil (Gold)	9
FloMAX R-Series Connectors - Transmission Fluid (Violet)	9
FloMAX Flush Face Connectors.....	10
FloMAX Flush Face Grease Connectors.....	11
FloMAX 3/4" Connectors.....	11
FloMAX Universal Drain Nozzle.....	12
JIC Bulkhead Receiver	12
FloMAX High-Flow Series.....	13

FloMAX Fuelling System FloMAX Fuelling System

FloMAX Fuelling System - Diesel Fuel Nozzle

Application

- On-site refuelling of construction, mining, forestry, and agricultural equipment.

Design

- Interchanges with Caterpillar® and Wiggins systems
- Integrated high-flow swivel
- Integrated sealing plug
- Delron® bushings eliminate metal-to-metal wear
- Plug/bumper assembly gives a complete nose seal

Materials

- Cast aluminium housing, anodised
- Anodised aluminium non-wear parts
- Heat-treated stainless steel wear components

Working Pressure

- Tested to 180 GPM

Options

- Stainless steel ball-lock and dog latch mechanisms are available



Size (inch)	Part Numbers	Thread	Description
1½	FN600	Female NPT	Fuel nozzle with swivel, plug & dog latch
	FN600BL	Female NPT	Fuel nozzle with swivel, plug & ball-lock
	FN600B-PLUG	-	Fuel nozzle sealing plug for FN600
	FN600B	-	Fuel nozzle sealing plug for FN600BL
	FN600-K1	-	Service kit
	FN600-K0	-	Rebuild tools
	FN600S	-	Fuel nozzle with swivel
	FN800-P	Female NPT	Fuel nozzle with 2" inlet swivel, plug & ball-lock

Product Group: AS04

FloMAX Fuelling System - Diesel Fuel Receivers

Application

- On-site refuelling of construction, mining, forestry and agricultural equipment.

Design

- Interchanges with Caterpillar® and Wiggins systems
- FR-RS receiver allows replacement of worn components without draining the fuel tank

Materials

- Available in anodised aluminium or nickel-plated steel
- O-ring sealed aluminium cap
- Plug has set screw attached vinyl coated cable lanyard
- FR-RS receiver has an aluminium base with a nickel-plated steel nose



One-Piece Body

Part Numbers	Description
FRS	Fuel receiver - steel
FRS-C	Fuel receiver - steel with cap
FRA	Fuel receiver - aluminium
FRA-C	Fuel receiver - aluminium with cap
FR-CAP	Fuel receiver cap

Product Group: AS04



Two-Piece Body

Part Number	Description
FR-RS-C	Fuel receiver with cap

Product Group: AS04

FloMAX Fuelling System FloMAX Fuelling System

Non-Interchange Diesel Fuel Nozzle and Receiver

Application

- Often used in biodiesel fuelling.

Features

- Designed to prevent fuel contamination
- Connects to the non-interchange receiver only
- Ball-lock design

Nozzle

Part Number	Description
FN600BL-NI	Ball-lock fuel nozzle with swivel & plug Product Group: AS04



Receiver - Anodised Aluminium

Part Number	Description
FRA-NI-C	One piece receiver with cap Product Group: AS04



FloMAX Fuelling System - Diesel High-Flow Fuel Nozzle

Application

- High-flow on-site refuelling of construction, mining, forestry, and agricultural equipment and machinery.

Design

- Stainless steel ball-lock design

- Stainless steel internal wear components
- Delron® bushings

Materials

- Cast aluminium housing
- Anodised aluminium non-wear parts

Working Pressure

- Tested to 1500 litres per minute

Size (inch)	Part Numbers	Thread	Description
2	FX1500SP	Female NPT	High-flow fuel nozzle with swivel & plug
	FX1500	Female NPT	High-flow fuel nozzle, no swivel or plug
	FX1500P	Female NPT	High-flow fuel nozzle with plug, no swivel
	FX1500S	Female NPT	High-flow fuel nozzle with swivel, no plug
	FX1500PLUG	-	Sealing plug for FX1500 Product Group: AS04



FloMAX Fuelling System - Diesel High-Flow Fuel Receiver

Application

- High-flow on-site refuelling of construction, mining, forestry and agricultural equipment and machinery.

Materials

- Aluminium anodised with stainless steel removable sleeve
- O-ring sealed aluminium cap
- Plug has set screw attached vinyl coated cable lanyard

Working Pressure

- Tested to 1500 litres per minute

Size (inch)	Part Numbers	Thread	Description
2	FRX	Female NPT	High-flow diesel fuel receiver
	FRX-C	Female NPT	High-flow diesel fuel receiver with cap
	FRXCAP	-	Cap to suit high-flow receiver Product Group: AS04



FloMAX Fuelling System FloMAX Fuelling System

FloMAX Fuelling System - Diesel Fuel Swivels

Features

- Stainless steel male threaded base and ball bearings
- Hard black anodised female threaded nut
- Fluorosilicone sealing o-rings

Materials

- Stainless steel and aircraft-grade aluminium



Standard



Double

Size (inch)	Part Numbers	Thread	Description
1½	FNS	NPT	Standard fuel swivel - male x female NPT
2 x 1½	FNS2	NPT	Standard fuel swivel - male x female NPT
1½	FN600S	NPT	FN600 fuel swivel - used with FN600 or FN600BL
	FNSID	NPT	Double fuel swivel - male x female NPT

Product Group: AS04

FloMAX Fuelling System - Gravity Fill Receivers

Application

- Small diameter for filling small fuel tanks.

Features

- Fits 1½" fuel receivers
- Allows transfer of fluid without using standard fuel receiver

Materials

- Aircraft-grade aluminium



90°



Straight

Size (inch)	Part Numbers	Style
1½	GFR-0	Straight
	GFR-45	45°
	GFR-90	90°
1	GFR1-0	Straight
	GFR1-45	45°
	GFR1-90	90°

Used with FN600 or FN600BL

Product Group: AS04

FloMAX Fuel Vent System

Application

- On-site refuelling of construction, mining, forestry, and agricultural equipment.

Design

- Billet cap provides superior impact resistance
- Easily serviced
- All metal construction
- Rigid ball age for positive seal

Options

- Available with threaded outlet, half coupling



VTT



VTX

Size (inch)	Part Numbers	Style
5	VT	5" Tube
7	VT7	7" Tube
9	VT9	9" Tube
5	VTT	Threaded outlet with 5" tube
7	VTT7	Threaded outlet with 7" tube
9	VTX-9	High-flow 9" tube

Product Group: AS04

FloMAX Fuelling System FloMAX Fuelling System

FloMAX Standard Series Connectors - Engine Oil (Red)

Design

- 4 colour-coded mating connectors
- Easily recognisable labelling and is fully compatible and interchangeable with industry standard
- Universally fits all crankcase receivers, both R-series and standard series
- Incorporates 10 locking balls with a 40% deeper engagement
- Larger diameter pullback lanyard
- Smoother actuation

Materials

- All metal construction
- Stainless steel wear components
- Bright red anodised aircraft-grade aluminium non-wear components
- Delron® bushings

Nozzles

Size (inch)	Part Numbers	Thread	Description
¾	ENBL	Male NPT	Engine nozzle ball-lock
	ENBL-P	Male NPT	Engine nozzle ball-lock with plug
-	ENBL-PLUG	-	Engine nozzle plug

Product Group: AS04



Receivers

Size (inch)	Part Numbers	Thread	Description
¾	ERS	Male NPT	Engine receiver
	ERS-C	Male NPT	Engine receiver with cap
-	ERS-CAP	-	Engine receiver cap
¾	ERJ	Male JIC	Engine receiver with JIC bulkhead base
	ERJ-C	Male JIC	Engine receiver with JIC bulkhead base & cap

Product Group: AS04



FloMAX Standard Series Connectors - Coolant Fluid (Teal)

Design

- Colour-coded mating connectors
- Ergonomically engineered pullbacks and caps
- The standard roll-pin locking mechanism

Materials

- Nickel-plated stainless steel nozzle and base
- Bright teal anodised aluminium

Nozzles

Size (inch)	Part Numbers	Thread	Description
½	CN	Male NPT	Coolant nozzle ball-lock
	CN-P	Male NPT	Coolant nozzle ball-lock with plug
-	CN-PLUG	-	Coolant nozzle plug

Product Group: AS04



Receivers

Size (inch)	Part Numbers	Thread	Description
½	CR-S	Male NPT	Coolant receiver
	CR-C	Male NPT	Coolant receiver with cap
-	CR-CAP	-	Coolant receiver cap

Product Group: AS04



FloMAX Fuelling System FloMAX Fuelling System

FloMAX Standard Series Connectors - Hydraulic Oil (Gold)

Design

- Easily recognisable labelling
- Fully compatible and interchangeable with industry standard
- Ergonomically engineered pullbacks and caps
- 10 steel dog latching mechanism
- Colour-coded mating connectors

Materials

- All metal construction
- Stainless steel wear components
- Bright gold anodised aircraft-grade aluminium non-wear components
- Nickel-plated stainless steel wear components



Nozzles

Size (inch)	Part Numbers	Thread	Description
3/4	HN	Female NPT	Hydraulic nozzle
	HN-P	Female NPT	Hydraulic nozzle with plug
-	HN-PLUG	-	Hydraulic nozzle plug

Product Group: AS04

Receivers



Size (inch)	Part Numbers	Thread	Description
3/4	HR	Male NPT	Hydraulic receiver
	HR-C	Male NPT	Hydraulic receiver with cap
-	HR-CAP	-	Hydraulic receiver cap

Product Group: AS04

FloMAX Standard Series Connectors - Transmission Fluid (Violet)

Design

- Ergonomically engineered pullbacks and caps
- 6 steel dog latching mechanism
- Colour-coded mating connectors

Materials

- Nickel-plated stainless steel nozzle nose and base
- Bright violet anodised



Nozzles

Size (inch)	Part Numbers	Thread	Description
1/2	TN	Male NPT	Transmission nozzle
	TN-P	Male NPT	Transmission nozzle with plug
-	TN-PLUG	-	Transmission nozzle plug

Product Group: AS04

Receivers



Size (inch)	Part Numbers	Thread	Description
1/2	TR	Male NPT	Transmission receiver
	TR-C	Male NPT	Transmission receiver with cap
-	TR-CAP	-	Transmission receiver cap

Product Group: AS04

FloMAX Fuelling System FloMAX Fuelling System

FloMAX R-Series Connectors - Engine Oil (Red)

Design

- Fully compatible and interchangeable with industry standard R-Series connectors
- Colour-coded and labelled mating components provide for quick and positive identification
- All metal construction ensures long and reliable performance
- Ergonomically engineered pullbacks and caps
- Standard roll-in locking mechanism

Materials

- Stainless steel and anodised aircraft-grade aluminium

Nozzles

Size inch	Part Numbers	Thread	Description
3/4	R-EN	Female NPT	R-Series engine nozzle ball-lock
	R-EN-P	Female NPT	R-Series engine nozzle ball-lock with plug
	R-EN-PLUG	-	R-Series engine nozzle ball-lock

Product Group: AS04



Receivers

Part Numbers	Thread		Description
	Male	Female	
R-ER	1.625-12 UN-2A	1.312-12 UN-2B	R-Series engine receiver
R-ER-C	1.625-12 UN-2A	1.312-12 UN-2B	R-Series engine receiver with cap
R-ER-CAP	-	-	R-Series engine receiver cap

Product Group: AS04



FloMAX R-Series Connectors - Coolant Fluid (Teal)

Nozzles

Size inch	Part Numbers	Thread	Description
1/2	R-CN	Female NPT	R-Series coolant nozzle ball-lock
	R-CN-P	Female NPT	R-Series coolant nozzle ball-lock with plug
	R-CN-PLUG	-	R-Series coolant nozzle ball-lock

Product Group: AS04



Receivers

Part Numbers	Thread		Description
	Male	Female	
R-CR	1.187-12 UN-2A	.875-14 UN-2B	R-Series coolant receiver
R-CR-C	1.187-12 UN-2A	.875-14 UN-2B	R-Series coolant receiver cap

Product Group: AS04



FloMAX Fuelling System FloMAX Fuelling System

FloMAX R-Series Connectors - Hydraulic Oil (Gold)


Nozzles



Size (inch)	Part Numbers	Thread	Description
1	R-HN	Female NPT	Hydraulic nozzle
	R-HN-P	Female NPT	Hydraulic nozzle with plug
-	R- HN-PLUG	-	Hydraulic nozzle plug

Product Group: AS04

Receivers



Part Numbers	Thread		Description
	Male	Female	
R-HR	1.875-12 UN-2A	1.625-12 UN-2B	R-Series hydraulic receiver
R-HR-C	1.875-12 UN-2A	1.625-12 UN-2B	R-Series hydraulic receiver with cap
R-HR-CAP	-	-	R-Series hydraulic receiver cap

Product Group: AS04

FloMAX R-Series Connectors - Transmission Fluid (Violet)

Nozzles



Size (inch)	Part Numbers	Thread	Description
3/4	R-TN	Female NPT	Transmission nozzle
	R-TN-P	Female NPT	Transmission nozzle with plug
-	R-TN-PLUG	-	Transmission nozzle plug

Product Group: AS04

Receivers



Part Numbers	Thread		Description
	Male	Female	
R-TR	1.312-12 UN-2A	1.062-12 UN-2B	Transmission receiver
R-TR-C	1.312-12 UN-2A	1.062-12 UN-2B	Transmission receiver with cap
R-TR-CAP	-	-	Transmission receiver cap

Product Group: AS04

FloMAX Fuelling System FloMAX Fuelling System

FloMAX Flush Face Connectors

Features

- The new patented design uses an internally sealed ball-lock mechanism to ensure a clean and trouble-free performance
- All flush-face connectors have the same outside dimensions and weight
- 12 colour choices and sizes are available along with a universal evacuation nozzle
- Can be connected without pulling on the nozzle pull back
- Flush face nozzle and receiver available in JIC base configuration on request
- Can be connected or disconnected under pressure
- The high-flow, patented non-interchangeable feature means each colour will only mate with its corresponding coloured receiver or nozzle
- 500 PSI working pressure
- 50 GPM flow rate

Material

- Aircraft-grade aluminium and hardened stainless steel
- Size: 3/4" male NPT

Nozzles

Size (inch)	Part Numbers	Thread (male)	Colour
3/4	FLN-1	NPT	Red
	FLN-2	NPT	Gold
	FLN-3	NPT	Teal
	FLN-4	NPT	Violet
	FLN-5	NPT	Navy
	FLN-6	NPT	Brown
	FLN-7	NPT	Blue/Grey
	FLN-8	NPT	Clear
	FLN-9	NPT	Green
	FLN-10	NPT	Grey
	FLN-11	NPT	Bronze
	FLN-12	NPT	Orange
	FLN-16EVAC	NPT	Flush face evacuation nozzle NPT
FLNJ-EVAC	JIC	Flush face evacuation nozzle JIC	


Product Group: AS04



Receivers

Size (inch)	Part Numbers	Thread (male)	Colour
3/4	FLR-C-1	NPT	Red
	FLR-C-2	NPT	Gold
	FLR-C-3	NPT	Teal
	FLR-C-4	NPT	Violet
	FLR-C-5	NPT	Navy
	FLR-C-6	NPT	Brown
	FLR-C-7	NPT	Blue/Grey
	FLR-C-8	NPT	Clear
	FLR-C-9	NPT	Green
	FLR-C-10	NPT	Grey
	FLR-C-11	NPT	Bronze
	FLR-C-12	NPT	Orange

Product Group: AS04



All receivers supplied with cap and lanyard

FloMAX Fuelling System FloMAX Fuelling System

FloMAX Flush Face Grease Connectors

Design

- Can be connected and disconnected under pressure
- Patented design uses an internally sealed ball-lock mechanism to ensure trouble-free performance in even the harshest conditions
- The receiver has a built-in check valve
- 1" female NPT on both receiver and nozzle for maximum flow and adaptability
- Fail-safe shut-off for safety
- Flush face design helps ensure vehicle and port cleanliness

Materials

- Stainless steel construction



Nozzles

Size (inch)	Part Numbers	Thread	Colour
1	FLNG-1	Female NPT	Blue
	FLNG-2	Female NPT	Orange

Product Group: AS04



Receivers

Size (inch)	Part Numbers	Thread	Colour
1	FLRG-1	Female NPT	Blue
	FLRG-2	Female NPT	Orange

Product Group: AS04

FloMAX 3/4" Connectors

Specifications

- Consists of 6 nozzles and receivers
- Colour-coded for quick identification of mating parts
- Will only couple with their matching colour component
- Protection against cross-contamination

Materials

- All metal construction using stainless steel and anodised aircraft-grade aluminium

Working Pressure

- Maximum flow rate of 50 GPM
- Working pressure rating of 500 PSI



Nozzles

Size (inch)	Part Numbers	Thread	Description
3/4	ENBL-P	Male NPT	Red nozzle with plug
	ENBL-P2	Male NPT	Gold nozzle with plug
	ENBL-P3	Male NPT	Teal nozzle with plug
	ENBL-P4	Male NPT	Violet nozzle with plug
	ENBL-P5	Male NPT	Navy nozzle with plug
	ENBL-P6	Male NPT	Copper nozzle with plug

Product Group: AS04



Receivers

Size (inch)	Part Numbers	Thread	Description
3/4	ERS-C	Male NPT	Red receiver with plug
	ERS-C2	Male NPT	Gold receiver with plug
	ERS-C3	Male NPT	Teal receiver with plug
	ERS-C4	Male NPT	Violet receiver with plug
	ERS-C5	Male NPT	Navy receiver with plug
	ERS-C6	Male NPT	Copper receiver with plug

Product Group: AS04

FloMAX Universal Drain Nozzle

Application

- Used to drain multiple fluids and incorporates a one-way check valve to prevent backflow and potential fluid cross-contamination.

Design

- Universal evacuation nozzle that will connect with all 3/4" ERS series receivers
- Ergonomically engineered pullbacks and caps
- The standard roll-pin locking mechanism

Materials

- Non-wear components are aircraft-grade aluminium
- All wear components are in stainless steel
- Black anodised

Size (inch)	Part Numbers	Thread	Description
3/4	UN34-P	Male NPT	Universal extraction nozzle with plug
	UN34	Male NPT	Universal extraction nozzle

Product Group: AS04



JIC Bulkhead Receiver

Size (inch)	Part Numbers	Thread	Description
3/4	ERJ-C	Male JIC	Red receiver with JIC bulkhead base, locknut & cap
	ERJ-C2	Male JIC	Gold receiver with JIC bulkhead base, locknut & cap
	ERJ-C3	Male JIC	Teal receiver with JIC bulkhead base, locknut & cap
	ERJ-C4	Male JIC	Violet receiver with JIC bulkhead base, locknut & cap
	ERJ-C5	Male JIC	Navy receiver with JIC bulkhead base, locknut & cap
	ERJ-C6	Male JIC	Copper receiver with JIC bulkhead base, locknut & cap

Product Group: AS04



FloMAX Flush Face Connectors

- Internally sealed ball lock mechanism
- 12 colour choices and sizes, with a universal evacuation nozzle
- Can be connected or disconnected under pressure



FloMAX Fuelling System FloMAX Fuelling System

FloMAX High-Flow Series

Application

- The high-flow series of connectors have the same non-interchangeable features as the 3/4" series but are in a higher flowing 1" NPT size.

Specifications

- Consists of 7 nozzles & receivers
- Colour-coded for quick identification of mating parts
- Will only couple with their matching colour component
- Protection against cross-contamination

Design

- Nozzle/receiver combination has a flow area equivalent to a 1" schedule 80 pipe
- Nozzle incorporates a ball-lock mechanism to ensure smooth & reliable operation
- Ergonomically engineered pullbacks and caps
- Nozzle Size: 100mm long, 64mm diameter, 57mm hex
- Receiver Size: 86mm long, 47mm diameter, 51mm hex

Connections

- Nozzle: 1" female NPT
- Receiver: 1" male NPT, with a 1" female NPT threaded base

Pressure Ratings

- Working Pressure: 500 PSI
- Burst Pressure: minimum 1500 PSI

Materials

- All metal construction using
- Bright red anodised aircraft-grade aluminium non-wear components



Nozzle



Receiver

Size (inch)	Part Numbers		Thread	Colour
	Nozzle	Receiver		
1	HFN-P1	HFR-C1	NPT	Red
	HFN-P2	HFR-C1	NPT	Gold
	HFN-P3	HFR-C1	NPT	Teal
	HFN-P4	HFR-C1	NPT	Viole
	HFN-P5	HFR-C1	NPT	Navy
	HFN-P6	HFR-C1	NPT	Copper
	HFN-P7	HFR-C1	NPT	Blue/Grey

Product Group: AS04

FloMAX System

Durable fuelling & fluid management systems that thrive in harsh mining conditions.





The Right Connection®

Dixon (Asia Pacific) Pty Ltd

170 Francis Road
Wingfield SA 5013

1300 134 651

dixonvalve.com.au

South Australia, Adelaide

(Head Office)
170 Francis Road
Wingfield SA 5013

Queensland, Brisbane

6 Union Circuit
Yatala QLD 4207

Queensland, Mackay

38 John Vella Drive
Paget QLD 4740

Victoria, Melbourne

13 Commercial Drive
Dandenong VIC 3175

Western Australia, Perth

19 Baile Road
Canning Vale WA 6155

New South Wales, Sydney

15 Watsford Road
Campbelltown NSW 2560