

Gauges & Thermometers

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions.

Dry Gauges

<u>styles</u>

- standard
- Flutterguard[™]
- Contractor Pressure
- Compound •
- Vacuum
- Welding

materials

- ABS
- Brass •
- Stainless steel

mount type

- lower
- center back •



Welding gauge



General Purpose digital gauge



Contractor Pressure gauge



Vacuum gauge



Flutterguard™ gauge



Stainless Steel Standard gauge

face size

- 11/2"
- 2" •
- 21/2"
- 31/2"
- 4½"

(contractor pressure gauge only)



Brass Standard gauge



Standard center back mount gauge



Compound gauge

Liquid Filled Gauges

<u>styles</u>

standard

mount type

- lower •
- center back



gauge

materials ABS

- Brass
- Stainless steel



- 21/2" 4"



Thermometers & Miscellaneous

thermometers

- bi-metal
 - model 30
 - model 31
 - model 50
 - model 52
 - pocket
 - magnetic surface mount
 - · threaded thermowells
 - 180° steam gauge siphon



Bi-metal thermometer

180° steam gauge siphon



thermometer





threaded thermowells



Dixon Valve & Coupling Co. 800 High Street • Chestertown, MD 21620 800.355.1991 Fax: 800.283.4966 www.dixonvalve.com

Printed in the USA

Hose Coupling **Safety**

- Use Dixon couplings, retention devices and accessory products only for their intended service.
- All recommendations of the Hose Manufacturer. and the Coupling Manufacturer, must be employed with regards to Size, Temperature, Application, Media, and **P**ressure when selecting the components for a hose assembly.
- All finished hose assemblies should be tested in accordance with the **R**ubber **M**anufacturers Association recommendations.
- All hose assemblies should be thoroughly inspected prior to each use to insure they are undamaged, and properly coupled.
- Use safety clips on couplings, and King Safety Cables on assemblies where required by the manufacturer. as well as State and Federal regulations.
- Call Dixon (1-800-355-1991) for advice on couplings, retention devices, and accessories for your application.

© 2012 DVCC