DATA SHEET Tef-Gel™

Anti Seize Assembly Lubricant

Tef-Gel[™] is a white, extremely high viscosity gel. It is applied to but not limited to fastenings, fittings and electrical connectors in high corrosive environments to ensure protection, serviceability & presentation of assembled hardware. Providing industrial strength protection.



Tube Size (grams)	Part Number
10 G	TEFGEL-10
30 G	TEFGEL-30
60 G	TEFGEL-60
120 G	TEFGEL-120
320 G	TEFGEL-320

Applications

- Fastenings
- Fittings
- Electrical connectors
- Around the home & garden
- Boat & Jetski
- TrailerCaravan
- Caravar

Features

• Non-toxic and non-harmful to marine, and land based ecosystems and us

The Right Connection

- Non-reactive and chemically stable
- · Has an indefinite shelf life and working life
- Contains PTFE (Teflon®) and 0% volatile solvents, no silicones, or petroleum solvents to evaporate
- Will not cold flow or dry out, giving long term protection of hardware for future disassembly
- · Industrial grade, non-hazardous, assembly lubricant

How it works

- · Prevents corrosion between dissimilar metals
- Galling of all grades of stainless steel
- Act as an assembly lubricant (anti-seize for ease of maintenance)
- · Protect electrical connectors from corrosion

Sizes

- 10 gram tube
- 30 gram tube
- 60 gram tub
- 120 gram tube
- 320 gram gun cartridge

Temperature

Working temperature -60° to 280°C

Approvals

AS/NZS 4020:2005 potable water certificate

Product Code: AS25

Dixon

1300 134 651 customerservice@dixonvalve.com.au dixonvalve.com.au