

Locking Cam Arm Velcro® Straps

B



coupler sold separately

Applications:	<ul style="list-style-type: none"> • use with cam and groove couplers to prevent spills, secure from damage, and hold in place during transport
Features:	<ul style="list-style-type: none"> • used on the female end of the cam and groove coupler • high visibility orange hook and loop with metal buckle provide strength, durability and long life • temperature range: -70°F to 200°F (-57°C to 93°C)

Length (inch)	Used On	Part No.	Price \$
18	fits up to 3" coupler	CVS18	11.60
36	fits up to 8" coupler	CVS36	14.14

Price Group: SD
AL02

Abrasion Resistant Inserts



400-A-INSERT



400-C-INSERTAL

Features:	<ul style="list-style-type: none"> • extends the life of adapters when transferring proppant to storage tanks • available for multiple adapter and multiple coupler materials
Materials:	<ul style="list-style-type: none"> • UHMW polyethylene

Part No.	Description	Price \$
400-A-INSERT	to be used with 400-A-AL, 400-A-BR, 400-A-MI, 400-A-SS	66.00
400-C-INSERTAL	to be used with 400-C-AL	97.00
400-C-INSERTMI	to be used with 400-C-MI	147.30

Price Group: CG
AL01

For technical, application and material guidelines, please refer to page 82

