

King Crimp™ Style Sleeves



Only use the crimp style shanks with the crimp style sleeves and ferrules.
Due to differences in dimensions and tolerances for safety reasons, DO NOT interchange other manufacturer's products with Dixon™ products.

D

Hose ID (inch)	Hose OD (mm)		Carbon Steel		304 Stainless Steel		WP (PSI)		Sleeve ID (mm)	Sleeve Wall Thickness (mm)	Sleeve Overall Length (mm)
	From	To	Part No.	Price \$	Part No.	Price \$	Cam & Groove ¹	KC Nipple ²			
1	30.56	31.75	CS100-1CS	9.07	CS100-1SS	18.14	*	*	33.40	1.57	63.5
1	32.15	33.34	CS100-2CS	9.07	CS100-2SS	18.14	*	*	34.90	1.57	63.5
1	33.73	34.93	CS100-3CS	9.07	CS100-3SS	18.14	*	*	36.50	1.57	63.5
1	35.32	36.51	CS100-4CS	9.07	CS100-4SS	18.14	*	*	38.10	1.57	63.5
1	36.91	38.10	CS100-5CS	9.07	CS100-5SS	18.14	*	*	39.70	1.57	63.5
1	38.50	39.69	CS100-6CS	9.07	CS100-6SS	18.14	*	*	42.30	1.57	63.5
1	40.08	41.28	CS100-7CS	9.07	CS100-7SS	18.14	*	*	42.90	1.57	63.5
1	41.67	42.86	CS100-8CS	9.07	CS100-8SS	18.14	*	*	44.50	1.57	63.5
1	43.26	44.45	CS100-9CS	9.07	CS100-9SS	18.14	*	*	46.10	1.57	63.5
1	44.85	46.03	CS100-10CS	9.07	CS100-10SS	18.14	*	*	47.60	1.57	63.5
1¼	30.56	42.86	CS125-3CS	28.21	CS125-3SS	22.17	250	300	44.45	1.57	63.5
1¼	43.26	44.45	CS125-4CS	28.21	CS125-4SS	22.17	250	300	46.05	1.57	63.5
1¼	44.85	46.04	CS125-5CS	28.21	CS125-5SS	22.17	250	300	47.63	1.57	63.5
1¼	46.43	47.63	CS125-6CS	28.21	CS125-6SS	22.17	250	300	49.23	1.57	63.5
1½	41.68	42.87	CS150-1CS	15.11	CS150-1SS	18.14	250	300	44.45	1.57	63.5
1½	43.26	44.45	CS150-2CS	15.11	CS150-2SS	18.14	250	300	46.05	1.57	63.5
1½	44.85	46.04	CS150-3CS	15.11	CS150-3SS	18.14	250	300	47.63	1.57	63.5
1½	46.44	47.63	CS150-4CS	15.11	CS150-4SS	18.14	250	300	49.23	1.57	63.5
1½	48.03	49.22	CS150-5CS	15.11	CS150-5SS	18.14	250	300	50.80	1.57	63.5
1½	49.61	50.80	CS150-6CS	15.11	CS150-6SS	18.14	250	300	52.40	1.57	63.5
1½	51.20	52.39	CS150-7CS	15.11	CS150-7SS	18.14	250	300	53.98	1.57	63.5
1½	52.79	53.98	CS150-8CS	15.11	CS150-8SS	18.14	250	300	55.58	1.57	63.5
1½	55.96	57.15	CS150-10CS	15.11	CS150-10SS	18.14	250	300	58.75	1.57	63.5
1½	57.55	58.74	CS150-11CS	15.11	CS150-11SS	18.14	250	300	60.33	1.57	63.5
1½	59.14	60.33	CS150-12CS	15.11	CS150-12SS	18.14	250	300	61.93	1.57	63.5
2	55.96	57.15	CS200-1CS	38.29	CS200-1SS	22.17	250	250	58.75	1.57	63.5
2	57.55	58.74	CS200-2CS	12.09	CS200-2SS	22.17	250	250	60.33	1.57	63.5
2	60.72	61.91	CS200-4CS	12.09	CS200-4SS	22.17	250	250	63.50	1.57	63.5
2	62.31	63.50	CS200-5CS	12.09	CS200-5SS	22.17	250	250	65.10	1.57	63.5
2	63.90	65.09	CS200-6CS	13.10	CS200-6SS	22.17	250	250	66.68	1.57	63.5
2	65.48	66.68	CS200-7CS	12.09	CS200-7SS	22.17	250	250	68.28	1.57	63.5
2	67.07	68.26	CS200-8CS	12.09	CS200-8SS	22.17	250	250	69.85	1.57	63.5
2	68.66	69.85	CS200-9CS	12.09	CS200-9SS	25.19	250	250	71.45	1.57	63.5
2	70.25	71.44	CS200-10CS	12.09	CS200-10SS	22.17	250	250	73.03	1.57	63.5
2	71.83	73.03	CS200-11CS	12.09	CS200-11SS	22.17	250	250	74.63	1.57	63.5
2	73.42	74.61	CS200-12CS	12.09	CS200-12SS	22.17	250	250	76.20	1.57	63.5

Price Group: SD

AU06

* Consult Dixon™ for pressure rating.

¹ Based on using crimp cam & groove shanks

² Based on using King™ combination nipples

