

## A Rubber Straight Radiator Hose (A112)



<b>Application:</b>	Recommended for handling hot water, anti-freeze etc. in cooling systems.
<b>Tube:</b>	NR / EPDM
<b>Reinforcing:</b>	High strength synthetic yarn
<b>Cover:</b>	NR / EPDM
<b>Temperature:</b>	-40°C to 100°C
<b>Standards:</b>	ISO/FDIS 4081:2005(e) Type 1 = -40° to 100°C

Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Length (mtr)	Price \$ per mtr
	ID	OD	PSI	MPa				
A11219	19	29	72	0.5	217	228 <sup>1</sup>	0.914	24.37
A11222	22	32	72	0.5	217	264 <sup>1</sup>	0.914	26.70
A11225	25	35	72	0.5	217	300 <sup>1</sup>	0.914	27.08
A11229	29	38	72	0.5	217	348 <sup>1</sup>	0.914	28.21
A11232	32	44	72	0.5	217	384 <sup>1</sup>	0.914	33.29
A11235	35	48	72	0.5	217	420 <sup>1</sup>	0.914	36.67
A11238	38	51	72	0.5	217	456 <sup>1</sup>	0.914	37.80
A11241	41	54	72	0.5	217	492 <sup>1</sup>	0.914	41.19
A11244	44	57	72	0.5	217	528 <sup>1</sup>	0.914	42.88
A11248	48	60	72	0.5	217	576 <sup>1</sup>	0.914	45.13
A11251	51	63	72	0.5	217	612 <sup>1</sup>	0.914	47.39
A11254	54	67	72	0.5	217	648 <sup>1</sup>	0.914	51.90
A11257	57	70	72	0.5	217	684 <sup>1</sup>	0.914	55.28
A11260	60	73	72	0.5	217	720 <sup>1</sup>	0.914	57.55
A11263	63	76	72	0.5	217	756 <sup>1</sup>	0.914	59.80
A11267	67	79	72	0.5	217	804 <sup>1</sup>	0.914	65.45
A11270	70	82	72	0.5	217	840 <sup>1</sup>	0.914	68.83
A11273	73	86	72	0.5	217	876 <sup>1</sup>	0.914	72.21
A11276	76	89	72	0.5	217	912 <sup>1</sup>	0.914	76.72

<sup>1</sup> Denotes figure is calculated as theoretical.

Price Group: HR  
DB01

Complete hose data specification sheets are available upon request.



1300 134 651  
dixonvalve.com.au

All prices exclude GST.  
ADPL718