

Grooved Butterfly Valves C/W Gear Operator Fig HGG

Design:	Gear operated butterfly valve
End Connection:	Grooved
Body Materials:	Ductile iron body and disc
Seats & Trim:	EPDM encapsulated
Temperature:	Max 120°C
Pressure:	Max 2100kPa (300 PSI)
Application:	Water, air and neutral liquids

Face to Face Dim	Part No.	Size NB (mm)	Price \$
115	VGBFNM-114-GEAR	100	766.37
145	VGBFNM-165-GEAR	150	1291.26
148	VGBFHP-200-GOP	200	1449.00
159	VGBFHP-250-GOP	250	2074.44
159	VGBFHP-300-GOP	300	2513.73

Price Group: FE
VF04



Grooved Butterfly Valves C/W Lever & Notch Plate Fig HGL

Design:	Grooved lever operated butterfly valve
End Connection:	Grooved
Body Materials:	Ductile iron body and disc
Seats & Trim:	EPDM encapsulated
Temperature:	Max 120°C
Pressure:	Max 2100kPa (300 PSI)
Application:	Water, air and neutral liquids

Face to Face Dim	Part No.	Size NB (mm)	Price \$
85	VGBF-60-LEVER	50	243.74
96	VGBF-76-LEVER	65	279.29
96	VGBF-88-LEVER	80	385.93
115	VGBF-114-LEVER	100	475.56
145	VGBF-165-LEVER	150	890.30
148	VGBF-219-LEVER	200	1127.32

Price Group: FE
VF04



M