

Test and Drain Valve - Fig BH-6

Design:	Tamper resistant sight glass Quarter turn handle from test to drain
End Connection:	2" BSP Male x Female
Body Material:	Brass body
Pressure:	Working pressure 300 PSI, tested to 400 PSI
Application:	To test water flow through sprinkler systems and system drain points

Size (mm)	Part No.	Working Pressure		Price \$
		PSI	MPa	
50	V50TD	300	2.0	391.48

Price Group: SD
VB10




Drum Gate Valves

Design:	Manually operated gate valve. Black Japanned finish.
End Connection:	Male NPT Thread
Body Material:	Malleable Iron
Pressure:	Suitable only for fluid head pressure in drum
Application:	For drawing non-flammable liquids from drums and tanks

NPT Size (mm)	Part No.	Price \$
50	D75	244.82

Price Group: SD
AU02



Brass Solenoid Valves - Fig B35

End Connection:	BSP Female
Body Material:	Brass, differential NC & NO
Application:	Air & fluid

Size (mm)	Part No.	Type	Price \$
Normally Closed			
15	VSOL-15	24 Volt DC	252.41
15	VSOL-15-M0	24 Volt DC c/w manual override	442.13
20	VSOL-20	24 Volt DC	424.44
15	VSOL-8615-NC	24 Volt AC	336.02
25	VSOL-8616-NC	24 Volt AC	424.44
40	VSOL-8618-NC	24 Volt AC	848.88
Normally Open			
20	VSOL-8715-NO	24 Volt AC	512.86
25	VSOL-8716-NO	24 Volt AC	512.86
40	VSOL-8718-NO	24 Volt AC	990.36

Price Group: SD
VB10



M