

Standard BSP Dixon™ Type A

Male Adaptor x Female BSP									
Size (mm)	Max WP PSI	Aluminium Die Cast		Bronze Sand Cast		Stainless Steel		Brass	
		Part No.	Price \$	Part No.	Price \$	Part No.	Price \$	Part No.	Price \$
15	150	ALDC050A	8.08	BR050A	14.72	SS050A	20.27	-	-
20	250	ALDC075A	6.65	BR075A	17.39	SS075A	20.74	BRSS075A	14.28
25	250	ALDC100A	6.68	BR100A	16.65	SS100A	24.04	BRSS100A	18.55
32	250	ALDC125A	9.22	BR125A	27.36	SS125A	39.65	BRSS125A	24.10
40	250	ALDC150A	8.02	BR150A	35.16	SS150A	39.12	BRSS150A	28.01
50	250	ALDC200A	8.04	BR200A	38.93	SS200A	48.56	BRSS200A	28.58
65	150	ALDC250A	20.36	BR250A	65.48	SS250A	93.17	BRSS250A	65.48
75	125	ALDC300A	17.42	BR300A	78.10	SS300A	110.05	BRSS300A	61.90
100	100	ALDC400A	33.29	BR400A	117.43	SS400A	166.86	BRSS400A	112.80
125	75	ALDC500A	45.39	BR500A	135.87	SS500A	336.57	-	-
150	75	ALDC600A	80.05	BR600A	229.63	SS600A	319.31	-	-

Price Group: CG AL12 **Price Group: CG AL06** **Price Group: CG AL05** **Price Group: CG AL14**



aluminum die cast



bronze sand cast



stainless steel



brass

B

Standard NPT Global Dixon™ Type A

Male Adaptor x Female NPT						
Size (mm)	Aluminium (Brass Handles)		Brass (Forged)		316 Stainless Steel	
	Part No.	Price \$	Part No.	Price \$	Part No.	Price \$
13	G50-A-AL	22.30	G50-A-BR	20.49	G50-A-SS	41.96
20	G75-A-AL	14.62	G75-A-BR	21.42	G75-A-SS	37.33
25	G100-A-AL	16.81	G100-A-BR	27.83	G100-A-SS	59.00
32	G125-A-AL	21.38	G125-A-BR	36.15	G125-A-SS	93.71
40	G150-A-AL	17.65	G150-A-BR	42.01	G150-A-SS	96.03
50	G200-A-AL	23.27	G200-A-BR	55.38	G200-A-SS	67.98
65	G250-A-AL	46.78	G250-A-BR	82.12	G250-A-SS	194.08
75	G300-A-AL	17.74	G300-A-BR	96.71	G300-A-SS	208.32
100	G400-A-AL	60.44	G400-A-BR	176.24	G400-A-SS	333.71
125	G500-A-AL	92.93	G500-A-BR	366.13	-	-
150	G600-A-AL	124.22	-	-	G600-A-SS	585.41
200	G800-A-AL	317.94	-	-	-	-

Price Group: CG AL07 **Price Group: CG AL14** **Price Group: CG AL05**



aluminum



brass (forged)



316 stainless steel

For technical, application and material guidelines, please refer to page 82

