


## External Notched Stems & Ferrules

This stem can be removed from a damaged hose by cutting away the ferrule, without necessarily damaging the fitting. After inspection to determine its suitability for reuse, it can be reinstalled into another hose by using a new ferrule. You can now stock one nipple and two ferrules, and thereby cover the same hose range with less inventory. 316 Stainless Steel Stem with wrench flat, 304 Stainless Steel Ferrule. You must purchase a fitting and the matching ferrule to create an assembly. Can be swaged-on or crimped-on; consult Dixon™ for specifications.

- For hose OD of 52.4 and below, these couplings are crimp only
- For hose OD of 52.8 and above, these couplings can be crimped or swaged

| Male NPT x Notched Shank |              |      |            |          |           |          |
|--------------------------|--------------|------|------------|----------|-----------|----------|
| Hose ID (mm)             | Hose OD (mm) |      | Ferrule    |          | Stem      |          |
|                          | From:        | To:  | Part No.   | Price \$ | Part No.  | Price \$ |
| 40                       | 48.8         | 54.8 | GAS2334NOS | 47.65    | RST150NOS | 81.81    |
| 40                       | 51.6         | 58.7 | GAS2370NOS | 52.10    | RST150NOS | 81.81    |
| 50                       | 61.9         | 67.5 | GAS2709NOS | 40.38    | RST200NOS | 102.26   |
| 50                       | 66.7         | 71.4 | GAS2885NOS | 118.43   | RST200NOS | 102.26   |
| 75                       | 86.9         | 93.3 | GAS3760NOS | 68.38    | RST300NOS | 184.07   |
| 75                       | 93.7         | 96.4 | GAS3885NOS | 80.21    | RST300NOS | 184.07   |

Price Group: SD  
AL03



| Male BSP x Notched Shank |              |      |            |          |            |          |
|--------------------------|--------------|------|------------|----------|------------|----------|
| Hose ID (mm)             | Hose OD (mm) |      | Ferrule    |          | Stem       |          |
|                          | From:        | To:  | Part No.   | Price \$ | Part No.   | Price \$ |
| 40                       | 48.8         | 54.8 | GAS2334NOS | 47.65    | RST150NOSA | 81.81    |
| 40                       | 51.6         | 58.7 | GAS2370NOS | 52.10    | RST150NOSA | 81.81    |
| 50                       | 61.9         | 67.5 | GAS2709NOS | 40.38    | RST200NOSA | 102.27   |
| 50                       | 66.7         | 71.4 | GAS2885NOS | 118.43   | RST200NOSA | 102.27   |
| 75                       | 86.9         | 93.3 | GAS3760NOS | 68.38    | RST300NOSA | 184.07   |
| 75                       | 93.7         | 96.4 | GAS3885NOS | 80.21    | RST300NOSA | 184.07   |

Price Group: SD  
AL03

Price Group: SD  
AU03



## EZ Boss-Lock™ Swaged Type C

Developed specifically for chemical transport hoses having Crosslinked Polyethylene (XLPE) or Ultra High Molecular Weight Polyethylene (UHMW) tubes. Swaged Boss-Lock™ provides you with a permanently attached Cam and Groove fitting when superior coupling retention is required.

In testing tank transport hoses from a wide variety of manufacturers, the Swaged Boss-Lock™ fitting proved itself to be the clear winner in overall performance. Fittings are also available on special order for other sizes or hose OD's. Consult Dixon™ for pricing and availability.

| Coupler x Hose Shank with Ferrule |                          |                      |                      |          |
|-----------------------------------|--------------------------|----------------------|----------------------|----------|
| Size (mm)                         | Stainless Steel Part No. | Minimum Hose OD (mm) | Maximum Hose OD (mm) | Price \$ |
| 20                                | RC075EZ-70               | 27.78                | 39.69                | 185.63   |
| 25                                | RC100EZ-70               | 34.13                | 42.86                | 194.13   |

Price Group: SD  
AL03



## EZ Boss-Lock™ Swaged Type E

| Adaptor x Hose Shank with Ferrule |                          |                      |                      |          |
|-----------------------------------|--------------------------|----------------------|----------------------|----------|
| Size (mm)                         | Stainless Steel Part No. | Minimum Hose OD (mm) | Maximum Hose OD (mm) | Price \$ |
| 20                                | RE075-1370               | 27.78                | 34.13                | 126.16   |
| 25                                | RE100-1620               | 36.91                | 39.29                | 139.92   |
| 25                                | RE100-1770               | 39.69                | 42.86                | 108.72   |

Price Group: SD  
AL03



For technical, application and material guidelines, please refer to page 82

