Valves

409

Brass Ball Valve Female x Female BSP - AGA Approved





T Handle

Brass Ball Valve Screwed Male Design: Full Bore / Female BSP - AGA Approved



Design:		Full bore, blow	Full bore, blow-proof stem				
End C	onnectio	n: Female x Fen	Female x Female BSP				
Body I	Materials	Nickel plated	Nickel plated brass with stainless steel handle				
Seat &	Ball:	PTFE seat an	PTFE seat and chrome plated brass ball				
Tempe	erature:	-10°C to 110°	С				
Approv	vals:	AGA Certified					
Applic	ation:	Recommende	d for	general use	with water, o	oil & gas	
Lever Handle *							
Size				Working Pressure Price \$			
Si	ze	Part No		Working	Pressure	Drico ¢	
Si inch	ze mm	Part No.		Working psi	Pressure MPa	Price \$	
_	i i	Part No. BBVAGA006				Price \$ 11.39	
inch	mm			psi	MPa		
inch 1⁄4	mm 6	BBVAGA006		psi 600	MPa 4.1	11.39	
inch 1⁄4 3⁄8	mm 6 10	BBVAGA006 BBVAGA010		psi 600 600	MPa 4.1 4.1	11.39 11.64	
inch 1/4 3/8 1/2	mm 6 10 15	BBVAGA006 BBVAGA010 BBVAGA012		psi 600 600 600	MPa 4.1 4.1 4.1	11.39 11.64 13.56	
inch 1/4 3/8 1/2 3/4	mm 6 10 15 20	BBVAGA006 BBVAGA010 BBVAGA012 BBVAGA020		psi 600 600 600 600	MPa 4.1 4.1 4.1 4.1	11.39 11.64 13.56 18.99	

Superseded model will be supplied whilst stocks last - check with Dixon at time of order.

BBVAGA050

2

50

Size		Part No.	Working	Working Pressure		
inch	mm	Part No.	psi	MPa	Price \$	
1⁄4	6	BBVAGAT006	710	4.9	17.03	
3⁄8	10	BBVAGAT010	710	4.9	16.97	
1⁄2	15	BBVAGAT012	710	4.9	21.22	
3/4	20	BBVAGAT020	570	3.9	31.15	
1	25	BBVAGAT025	570	3.9	45.33	

600

4.1

Price Group: SD

154.68

Price Group: SD

End Connection:		Screwed Male/Female BSP.					
Body Materials:		Brass					
Seat & Trim:		PTFE Seats					
Temperature:		-20°C, 60°C (class T2 under EN331)					
Application:		Industrial pneumatic and hydraulic applications. Water, oil & gas.					
Size		Part No.		Working Pressure		Price \$	
inch	mm		Fart NO.		psi	MPa	Filce a
1/2	15	BB	BBVAGAMF012		710	4.9	24.32

inch	mm		psi	MPa	1 1100 \$
1/2	15	BBVAGAMF012	710	4.9	24.32
3⁄4	20	BBVAGAMF020	570	3.9	42.44
1	25	BBVAGAMF025	570	3.9	66.91
1½	40	BRBLMF040	363	2.5	126.68

Price Group: SD AR01

Brass Ball Valve Screwed Female BSP - AGA Approved



*Warning: the formation of ice in the plant can severely damage valves and piping. We also remind that the maximum working temperature in gas pipes permitted all regulations is 60°C. FETY ALERT

Design:	Full Bore				
End Connection:	Screwed Female BSP.				
Body Materials:	De-Zincified Brass with PTFE Seats				
Approvals:	AGA approved and Water Marked				
Application:	Industrial pneumatic & hydraulic applications. Water, oil & gas.				
Size	Working Pressure				
inch mm	Part No. psi MPa Price \$				

-			_		-	
1/2	15	VB-J360-015	i	230	1.6	14.67
3⁄4	20	VB-J360-020		230	1.6	20.73
1	25	VB-J360-025		230	1.6	35.40
1¼	32	VB-J360-032		230	1.6	58.62
11⁄2	40	VB-J360-040		230	1.6	91.91
2	50	VB-J360-050		230	1.6	148.05

Price Group: SD

VB08



1

Phone: 1300 134 651 www.dixonvalve.com

ADPL2013-14

Part numbers marked "i" are non stock. Enquire for availability. All prices exclude GST.